Hoarder (Bookmark-Senke)

```
services:
  web:
    image: ghcr.io/hoarder-app/hoarder:${HOARDER_VERSION:-release}
    restart: unless-stopped
    volumes:
      # By default, the data is stored in a docker volume called "data".
      # If you want to mount a custom directory, change the volume mapping to:
      # - /path/to/your/directory:/data
      - data:/data
    ports:
      - 3023:3000
    env_file:
      - stack.env
    environment:
      MEILI_ADDR: http://meilisearch:7700
      BROWSER_WEB_URL: http://chrome:9222
      # OPENAI_API_KEY: ...

      # You almost never want to change the value of the DATA_DIR variable.
      # If you want to mount a custom directory, change the volume mapping above instead.
      DATA_DIR: /data # DON'T CHANGE THIS
  chrome:
    image: gcr.io/zenika-hub/alpine-chrome:123
    restart: unless-stopped
    command:
      - --no-sandbox
      - --disable-gpu
      - --disable-dev-shm-usage
      - --remote-debugging-address=0.0.0.0
      - --remote-debugging-port=9222
      - --hide-scrollbars
  meilisearch:
    image: getmeili/meilisearch:v1.11.1
```

```
    restart: unless-stopped
    env_file:
      - stack.env
    environment:
      MEILI_NO_ANALYTICS: "true"
    volumes:
      - meilisearch:/meili_data

volumes:
  meilisearch:
  data:
```

.env

```
DATA_DIR=/data
MEILI_ADDR=http://127.0.0.1:7700
MEILI_MASTER_KEY=m2l...........VU3e
NEXTAUTH_URL=http://localhost:3000
NEXTAUTH_SECRET=8Fz.............c6qU
DISABLE_SIGNUPS=true
OPENAI_API_KEY=sk-svcacct-PZe_..........BO9AA
```

Revision #1
Created 2025-03-04 21:15:35 UTC
Updated 2025-03-04 21:16:36 UTC