

UpSnap WakeOnLan WOL

```
version: "3"
services:
  upsnap:
    container_name: upsnap
    image: ghcr.io/seriousm4x/upsnap:4
    network_mode: host
    restart: unless-stopped
    volumes:
      - ./data:/app/pb_data
      # # To use a non-root user, create the mountpoint first (mkdir data) so that it has the
right permission.
      # user: 1000:1000
    environment:
      - TZ=Europe/Berlin # Set container timezone for cron schedules
      # - UPSNAP_INTERVAL=@every 10s # Sets the interval in which the devices are pinged
      # - UPSNAP_SCAN_RANGE=192.168.1.0/24 # Scan range is used for device discovery on local
network
      # - UPSNAP_WEBSITE_TITLE=Custom name # Custom website title
      # # dns is used for name resolution during network scan
      # dns:
      # - 192.18.0.1
      # - 192.18.0.2
      # # you can change the listen ip:port inside the container like this:
    entrypoint: /bin/sh -c "./upsnap serve --http 0.0.0.0:5080"
    healthcheck:
      test: curl -fs "http://localhost:5080/api/health" || exit 1
      interval: 10s
      # # or install custom packages for shutdown
      # entrypoint: /bin/sh -c "apk update && apk add --no-cache <YOUR_PACKAGE> && rm -rf
/var/cache/apk/* && ./upsnap serve --http 0.0.0.0:8090"
```

Revision #1

Created 2023-11-21 21:29:15 UTC

Updated 2024-06-15 15:07:40 UTC